




ECM-BYT

Intel® Celeron®/Atom™ SoC Processors J1900/E3845 3.5" Micro Module



- > Onboard Intel® Celeron®/Atom™ SoC J1900/E3845 BGA Processor
- > One 204-pin DDR3L SODIMM Socket Supports Up to 8GB DDR3L 1066/ 1333 SDRAM
- > Dual View, 2-CH LVDS, CRT, HDMI
- > 2 x Gigabit Ethernet
- > HD Audio/ Fanless Operation
- > 1 CF, 1 SATA II, 1 Mini-PCIe, 1 USB 3.0, 5 USB 2.0, 4 COM, 8-bit GPIO

+ Spec

System	
Processor	Intel® Atom™ E3845 4-Core 1.91GHz processor Intel® Celeron® J1900 4-Core 2.0GHz processor
System Memory	1 x 204-Pin DDR3L 1066MHz SO-DIMM up to 8 GB or 1 x 204-Pin DDR3L 1333MHz SO-DIMM up to 8 GB Processor E3845 & J1900 only support 1333MHz
I/O Chip	EC ITE IT8528E
BIOS	AMI uEFI BIOS, 64Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec and 1sec. or 1min./step
H/W Status Monitor	Monitoring SYSTEM Temperature, Voltage and FAN Status with Auto Throttling Control
Expansion	
Expansion	1 x Mini PCIe Supports mSATA
Storage	
Storage	1 x CompactFlash Type I/II Socket
Touch Screen	
Built-in Touch controller(optional)	Chipset:PenMount 6000 Touch Screen Interface:With 5-pin 2.0mm Box Header (Can be Selected to Support 4/ 5Wire Touch Screen)
I/O	
USB	5 x USB 2.0 1 x USB 3.0
SATA	1 x SATA II
COM Port	1 x RS-232/422/485 3 x RS-232
DIO	1 x 8bit GPIO
MIO	1 x LPC 1 x PS2/ KB & MS
Display	
Chipset	Intel® Valleyview SoC integrated Graphics Supports dual display
Resolution	VGA:Max. resolution 2560x1080@ 60Hz HDMI:Max. resolution 1920x1200@ 60Hz LVDS:Max. resolution 1920x1080@ 60Hz CRT + LVDS; HDMI + LVDS; CRT + HDMI Dual-channel 18/ 24-bit LVDS
Audio	
Chipset	Realtek ALC892 Support 5.1-CH
Audio Interface	Mic-In, Line-In and Line-Out
Ethernet	
Chipset	2 x Intel® I211AT
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45
Mechanical & Environmental	
Power Requirement	+12V ~ +26V
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI3.0 Compliant
Power Type	AT/ATX
Operating Temp	0°C ~ 60°C (32°F ~ 140°F) -40°C ~ 85°C (-40°F ~ 185°F) (Optional for Wide Temperature Model)
Storage Temp	-40°C ~ 75°C (-40°F ~ 167°F)



Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (L x W)	5.7" x 4" (146mm x 101mm)
Weight	0.44lbs (0.2kg)
Certifications	
Certification Information	CE FCC Class B
Software Support	
OS Information	Win 10 Win 8 Win 7 Linux

+ Ordering

ECM-BYT-E3845-A1R
ECM-BYT W/I E3845/1SATA/4COM/A1

ECM-BYT-J1900-A1R
ECM-BYT W/D J1900/1SATA/4COM/A1

ECM-BYT-E3845W-A1R (Wide temp.-40~+85C)
ECM-BYT W/I E3845/4COM/WT/A1