

INDUSTRIAL TOUCH MONITOR

18,5" / 46,99 cm EP185WAD201-1-PCAP-U-DM (12036779)

Display

Active screen dimensions (horizontal x vertical) 408,96 x 230,04 mm Resolution (pixel) / format 1920 x 1080 / 16:9 Brightness (typical) 500 cd/m² Contrast ratio (typical) 1000:1 Color performance 16.7 Mio Viewing angle (typical) 89/89/89/89 °LRUD Backlight LED LED Life time 50.000 hrs Altitude Operation / storage: 10.000 ft / 30.000ft

Interface Board

Connectors DisplayPort 1.1a

Touch

Touch screen Projected capacitive
Touch interface USB B type female

Power

Power supply 12V DC +/-10% Power input 2.5mm DC Jack

Mechanics

Housing Open frame housing, black painted, VESA 100 and VESA 75

Protection glass 3mm tempered glass, anti-glare with ceramic printing

Weight 4kg

Environmental conditions

 Temperature (operating)
 0°C to +40°C

 Temperature (storage)
 -20°C to +60°C

 Humidity
 30-95%RH

 EMI
 EN61000-6-1. EN

EMI EN61000-6-1, EN61000-6-3
ROHS / REACH

■ EN61000-6-1

Options

12V DC power supply adaptor

Power cable for power supply adaptor

•







