



SPECIFICATION



PH800480T-013-IHB

7" - WVGA – RGB/TTL

Version: 1.8

Date: 03.08.2017

Note: This specification is subject to change without prior notice

SPECIFICATIONS


| | | |
|------------------------|---|--------------------------------|
| CUSTOMER | : | CDE012 |
| SAMPLE CODE | : | SH800480T013-IHB |
| MASS PRODUCTION CODE | : | PH800480T013-IHB |
| SAMPLE VERSION | : | 01 |
| SPECIFICATIONS EDITION | : | 008 |
| DRAWING NO. (Ver.) | : | LMD-PH800480T013-IHB (Ver.004) |
| PACKAGING NO. (Ver.) | : | PKG-PH800480T013-IHB (Ver.001) |

Customer Approved

Date:

| Approved | Checked | Designer |
|---------------------|-------------------|--------------------|
| 黃秋源 Oliver Huang | 石建莊 Stone Shin | 黃俊清 Ackey Huang |

- ☐ Preliminary specification for design input
☒ Specification for sample approval



POWERTIP TECH. CORP.

Headquarters:

No.8, 6th Road, Taichung Industrial Park,
Taichung, Taiwan
台中市 407 工業區六路 8 號

TEL: 886-4-2355-8168
FAX: 886-4-2355-8166

E-mail: sales@powertip.com.tw
[Http://www.powertip.com.tw](http://www.powertip.com.tw)

History of Version

[illegible]

Total: 30 Page

Contents

1. SPECIFICATIONS

- 1.1 Features
- 1.2 Mechanical Specifications
- 1.3 Absolute Maximum Ratings
- 1.4 DC Electrical Characteristics
- 1.5 Optical Characteristics
- 1.6 Backlight Characteristics
- 1.7 Touch Panel Characteristics

2. MODULE STRUCTURE

- 2.1 Counter Drawing
- 2.2 Interface Pin Description
- 2.3 Timing Characteristics

3. QUALITY ASSURANCE SYSTEM

- 3.1 Quality Assurance Flow Chart
- 3.2 Inspection Specification

4. RELIABILITY TEST

- 4.1 Reliability Test Condition

5. PRECAUTION RELATING PRODUCT HANDLING

- 5.1 Safety
- 5.2 Handling
- 5.3 Storage
- 5.4 Terms of Warranty

Appendix : LCM Drawing.
LCM Packaging Specifications.

1. SPECIFICATIONS

1.1 Features

| Item | Standard Value |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display Resolution | 800 * 3 (RGB) * 480 Dots |
| LCD Type | a-Si TFT , Normally white , Transmissive type |
| Screen size(inch) | 7.0 inch |
| Viewing Direction | 6 O'clock |
| Surface treatment | Anti-Glare |
| Color configuration | R.G.B. Vertical Stripe |
| Weight | - |
| Interface | 24 Bits RGB Interface |
| ROHS | THIS PRODUCT CONFORMS THE ROHS OF PTC Detail information please refer website : http://www.powertip.com.tw/news_detail.php?Key=1&cID=1 |

1.2 Mechanical Specifications

| Item | Standard Value | Unit |
|-------------------|----------------------------------|------|
| Outline Dimension | 164.9 (W) * 100.0 (L) * 4.95 (H) | mm |

LCD panel

| Item | Standard Value | Unit |
|-------------|------------------------|------|
| Active Area | 154.08 (W) * 85.92 (L) | mm |

Note : For detailed information please refer to LCM drawing.

1.3 Absolute Maximum Ratings

Module

| Item | Symbol | Condition | Min. | Max. | Unit | Remark |
|-----------------------|-----------------|-----------|------|-------|------|--------|
| Power Supply Voltage | VDD | GND=0 | -0.3 | +5.0 | V | - |
| Power Supply Voltage | VCC | GND=0 | -0.3 | +20.0 | V | |
| Operating Temperature | T _{OP} | - | -20 | +70 | °C | |
| Storage Temperature | T _{ST} | - | -30 | +80 | °C | |

The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

1.4 DC Electrical Characteristics

Module

GND = 0V, Ta = 25 °C

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit |
|-----------------------------------|-----------------|--------------|--------|------|--------|------|
| Power Supply for TFT Panel | VDD | GND=0V | 3.0 | 3.3 | 3.6 | V |
| Power Supply for Backlight Unit | VCC | GND=0V | 5 | 12 | 15 | V |
| Input Voltage for TFT Panel | V _{IH} | GND=0V | 0.7VDD | - | VDD | V |
| | V _{IL} | GND=0V | 0 | - | 0.3VDD | V |
| Supply Current for TFT Panel | IDD | IDD@VDD=3.3V | - | 110 | 165 | mA |
| Supply Current for Backlight Unit | ICC | ICC@VCC=5V | - | 850 | 1275 | mA |
| Supply Current for Backlight Unit | ICC | ICC@VCC=12V | - | 240 | 360 | mA |
| Input Voltage for PWM Signal | VPH | GND=0V | 1.2 | - | - | V |
| | VPL | GND=0V | - | - | 0.4 | V |
| Dimming Clock Rate | fP | GND=0V | 5 | - | 100 | KHz |

1.5 Optical Characteristics

TFT LCD Module

VDD = 3.3 V, Ta=25℃

| Item | | Symbol | Condition | Min. | Typ. | Max. | unit | |
|---------------------------------------------------------------------|--------|--------|----------------------------------------|------|------|------|-------------------|--------|
| Response time | Rise | Tr | - | - | 10 | 20 | ms | Note 2 |
| | Fall | Tf | | - | 15 | 30 | | |
| Viewing angle | Top | θY+ | CR ≥ 10 | 40 | 50 | - | Deg. | Note 4 |
| | Bottom | θY- | | 60 | 70 | - | | |
| | Left | θX- | | 60 | 70 | - | | |
| | Right | θX+ | | 60 | 70 | - | | |
| Contrast ratio | | CR | - | 400 | 500 | - | - | Note 3 |
| Color of CIE Coordinate (LCD & BL & TP) | White | X | VCC=12.0V PWM="High" (Duty=100%) | 0.25 | 0.30 | 0.35 | - | Note1 |
| | | Y | | 0.29 | 0.34 | 0.39 | | |
| | Red | X | | 0.52 | 0.57 | 0.62 | | |
| | | Y | | 0.30 | 0.35 | 0.40 | | |
| | Green | X | | 0.29 | 0.34 | 0.39 | | |
| | | Y | | 0.55 | 0.60 | 0.65 | | |
| | Blue | X | | 0.10 | 0.15 | 0.20 | | |
| | | Y | | 0.03 | 0.08 | 0.13 | | |
| Average Brightness Pattern=white display (LCD & BL & TP) *1 | | IV | VCC=12.0V PWM="High" (Duty=100%) | 640 | 800 | - | cd/m ² | Note1 |
| Uniformity (LCD & BL & TP) *2 | | △B | | 70 | - | - | % | Note1 |

Note 1:

*1 : $\Delta B = B(\min) / B(\max) * 100\%$


*2 : Measurement Condition for Optical Characteristics:

a : Environment: $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ / $60 \pm 20\% \text{R.H}$, no wind , dark room below 10 Lux at typical lamp current and typical operating frequency.

b : Measurement Distance: $500 \pm 50 \text{ mm}$, ($\theta = 0^{\circ}$)

c : Equipment: TOPCON BM-7 fast , (field 1°) , after 10 minutes operation.

d : The uncertainty of the C.I.E coordinate measurement ± 0.01 , Average Brightness $\pm 4\%$



To be measured at the center area of panel with a viewing cone of 1° by Topcon luminance meter BM-7, after 10 minutes operation (module)

Note2: Definition of response time:


The output signals of photo detector are measured when the input signals are changed from "black" to "white"(falling time) and from "white" to "black"(rising time), respectively. The response time is defined as the time interval between the 10% and 90% of Amplitudes.

Refer to figure as below:

Normally White



Normally Black




Note3: Definition of contrast ratio:

Contrast ratio is calculated with the following formula

$$\text{Contrast ratio (CR)} = \frac{\text{Photo detector output when LCD is at "White" state}}{\text{Photo detector output when LCD is at "Black" state}}$$

Note4: Definition of viewing angle:

Refer to figure as below:



1.6 Backlight Characteristics

Maximum Ratings


| Item | Symbol | Min. | Max. | Unit | Remark |
|---------------------|--------|------|------|------|---------|
| LED Forward Current | I_F | | 35 | mA | One LED |
| LED Reverse Voltage | V_R | | 10 | V | |

Electrical / Optical Characteristics

| Item | Symbol | Min. | Typ. | Max. | Unit | Remark |
|---------------|--------|-------|------|------|----------------|--------|
| LED Voltage | V_L | 14.7 | 18.0 | 19.2 | V | Note1 |
| LED Current | I_L | - | 140 | - | mA | - |
| LED life time | - | 50000 | - | - | H _r | Note2 |

Note 1: The LED Supply Voltage is defined by the number of LED at $T_a=25\text{ }^{\circ}\text{C}$ and $I_L=140\text{ mA}$.

Note 2: The "LED life time" is defined as the module brightness decrease to 50% original brightness at $T_a=25\text{ }^{\circ}\text{C}$ and $I_L=140\text{ mA}$. The LED life time could be decreased if operating I_L is larger than 140 mA.



1.7 Touch Panel Characteristics

1.7.1 Optical Characteristics

| Item | Specification |
|----------------|---------------|
| 1.Transparency | 80% Min |

1.7.2 Mechanical Characteristic

| Item | Specification |
|-----------------------|-------------------------------------------------------------------------------------------------------------------|
| 1.Input Method | Finger or stylus pen |
| 2.Hardness of surface | 3H -pressure 500g of ,45deg. |
| 3.Activation Force | 250gf less individual point with stylus pen(R0.8) Activation force guarantee area:3.0mm inside of Active Area. |
| 4.Linearity Force | 150gf less input with stylus pen(R0.8) Activation force guarantee area:3.0mm inside of Active Area. |

1.7.3 Electrical Characteristics

| Item | Specification |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.Rated Voltage | DC 5V(DC 7V Max) |
| 2.Resistance Between Terminals. | Direction X (Glass side): 500Ω~ 1000Ω |
| | Direction Y (Film side): 100Ω~ 500Ω |
| 3.Insulation Resistance | 20 MΩ or more (DC 25 V 1min) |
| 4.Linearity | ±1.5%. Linearity(%)= $\Delta V / (EV - SV) \times 100$. ΔV : The difference between the ideal voltage and measured voltage on the each measuring line. SV: Voltage of starting Points. EV: Voltage of Ending Points. (Test condition refers to 1.7.2 item4) |
| 5.Bouncing | <10ms (Tip R 3.75mm, hardness 10°~20°, silicon rubber ,500gf operation : 40 mm/sec) |

1.7.4 Reliability Characteristic


| NO | Test Item | Test Condition | Test Result |
|----|----------------------------------------|---------------------------------------------------------------------------------|-------------------------------|
| 1 | Hitting Durability | 1,000,000times min.(R 8 mm Silicon Rubber Hardness 60° 250gf 2times/sec). | Follow 1.7.3 item2 and item4. |
| 2 | Pen Sliding Durability | 100,000 times min(Tip R0.8mm). | Follow 1.7.3 item2 and item4. |
| 3 | Impact Resistance | φ9mm steel ball is dropped on the surface from 30 cm height at 1 time. | No Crack |
| 4 | Flexible pattern Bending Resistance | Bending 3 times by bending radius R1.0 mm | Follow 1.7.3 item2. |

1.7.5 Touch Panel Design/Handling Guide

- (1) Keep the gap, for example 0.2 to 0.3mm, between bezel edge and T/P edge.

The reason is to avoid the bezel edge from contacting T/P surface that may cause “short” with bottom layer

- (2) Insertion a cushion material is recommended.
- (3) The cushion material should be limited on the busbar insulation paste area. If it is over the transparent insulation paste area, a “short” may be occurred.
- (4) Do not to use an adhesive tape to bond it on the front of T/P and hang it to the housing bezel.
- (5) Never expand the T/P top layer (PET Film) like a balloon by internal air pressure. The life of the T/P will extremely decreasing.
- (6) Top layer, PET, dimension is changing base on environment temperature and humidity. Please avoid a stress from housing bezel to top layer, because it may cause “waving”.
- (7) The input to the Touch Panel sometimes distorts touch panel itself.
- (8) To use the stylus pen or fingernail sliding at the edge of the housing is prohibited. It would cause the cracking of the ITO coating and damage the touch panel. It also request not to press this area while assembling
- (9) Purpose: In order to prevent accidental use and performance deterioration, please keep the following precautions.



In order to prevent unusual performance degradation and malfunction of a touch panel, please carry out the set case designing and a touch panel assembling method after surely considering the definition of each area illustrated in above figure.

Area(a) : Active area

The active area is guaranteed the position data detectable precision, operation force and other operations. it is strongly recommended to place the operation button or menu keys within the active area. Due to structure, the active area is less durable at the edge or close to the edge.

Area(b) : Operation non-guaranteed area

This area does not guarantee a touch panel operation and its function. When this area is pressed, touch panel shows degradation of its performance and durability such as a pen sliding durability becomes about one-tenth compared with the active area (area-(a) as guaranteed area) and its operation force requires about double. About 0.5 mm outside from a boundary of the active area corresponds to this area.

Area(c) : Pressing prohibition area

The area which forbids pressing, because an excessive load is applied to a transparent electrode (ITO) and a serious damage is given to a touch panel function by pressing. About 0.5 mm outside from Operation non-guaranteed area .

Area(d) : Non-Active area

The area does not activate even if pressed.




2. MODULE STRUCTURE

2.1 Counter Drawing

2.1.1 LCM Mechanical Diagram

* See Appendix

2.1.2 Block Diagram



2.2 Interface Pin Description

TFT LCM Interface

| Pin# | Name | DESCRIPTION |
|------|------|---------------------------------------------------------------------------------------------------------|
| 1 | GND | Power Ground. |
| 2 | VDD | Power for Digital Circuit. |
| 3 | VDD | Power for Digital Circuit. |
| 4 | VCC | Power For LED backlight. |
| 5 | VCC | Power For LED backlight. |
| 6 | PWM | Shutdown & Dimming control input for backlight. Do not allow this pin to float. "Hi" =100%, "Low" = 0%. |
| 7 | GND | Power Ground. |
| 8 | R0 | Red Data. |
| 9 | R1 | Red Data. |
| 10 | R2 | Red Data. |
| 11 | R3 | Red Data. |
| 12 | GND | Power Ground. |
| 13 | R4 | Red Data. |
| 14 | R5 | Red Data. |
| 15 | R6 | Red Data. |
| 16 | R7 | Red Data. |
| 17 | GND | Power Ground. |
| 18 | G0 | Green Data. |
| 19 | G1 | Green Data. |
| 20 | G2 | Green Data. |
| 21 | G3 | Green Data. |
| 22 | GND | Power Ground. |
| 23 | G4 | Green Data. |
| 24 | G5 | Green Data. |
| 25 | G6 | Green Data. |
| 26 | G7 | Green Data. |
| 27 | GND | Power Ground. |
| 28 | B0 | Blue Data. |
| 29 | B1 | Blue Data. |


| Pin# | Name | DESCRIPTION |
|------|-----------------------|------------------------------------------------------------------|
| 30 | B2 | Blue Data. |
| 31 | B3 | Blue Data. |
| 32 | GND | Power Ground. |
| 33 | B4 | Blue Data. |
| 34 | B5 | Blue Data. |
| 35 | B6 | Blue Data. |
| 36 | B7 | Blue Data. |
| 37 | GND | Power Ground. |
| 38 | HS | Line synchronization signal. Horizontal Sync Input. |
| 39 | VS | Frame synchronization signal. Vertical Sync Input. |
| 40 | GND | Power Ground. |
| 41 | DE | Display enable pin from controller. Data Input Enable. |
| 42 | GND | Power Ground. |
| 43 | DCLK | Sample clock. Data shall be latched at the falling edge of DCLK. |
| 44 | GND | Power Ground. |
| 45 | CS(NC) / ID1 | No Function./ ID[4:1]These pins select LCM type. |
| 46 | SDIN(NC) / ID2 | No Function./ ID[4:1]These pins select LCM type. |
| 47 | SCK(NC) / ID3 | No Function ./ ID[4:1]These pins select LCM type. |
| 48 | DISPLAY CONTROL / ID4 | Display Enable(Hi Active)/ ID[4:1]These pins select LCM type. |
| 49 | /RESET | Global Reset(Low Active). |
| 50 | GND | Power Ground. |

4-Wire Resistive Touch Screen (RTP) Interface

| Pin No. | Symbol | Function |
|---------|--------|--------------|
| 1 | XR | TP: X right |
| 2 | YD | TP: Y bottom |
| 3 | XL | TP: X left |
| 4 | YU | TP: Y top |

2.3 Timing Characteristics

2.3.1 Signal AC Characteristics




| Item | Symbol | Values | | | Unit | Remark |
|-------------------------|--------|--------|-----|-----|------|--------------------|
| | | Min | Typ | Max | | |
| HS setup time | Thst | 8 | - | - | ns | |
| HS hold time | Thhd | 8 | - | - | ns | |
| VS setup time | Tvst | 8 | - | - | ns | |
| VS hold time | Tvhd | 8 | - | - | ns | |
| Data setup time | Tdsu | 8 | - | - | ns | |
| Data hold time | Tdhd | 8 | - | - | ns | |
| DE setup time | Tesu | 8 | - | - | ns | |
| DE hold time | Tehd | 8 | - | - | ns | |
| DVDD Power On Slew rate | TPOR | - | - | 20 | ms | From 0 to 90% DVDD |
| RESET pulse width | TRst | 1 | - | - | ms | |
| DCLK cycle time | Tcph | 20 | 30 | - | ns | |
| Low Level Width | Tcwl | 8 | - | - | ns | |
| High Level Width | Tcwh | 8 | - | - | ns | |
| DCLK pulse duty | Duty | 40 | 50 | 60 | % | Tcwh / Tcph |

2.3.2 Input Timing Setting


| Item | Symbol | Values | | | Unit | Remark |
|-------------------------|--------|--------|------|------|------|--------|
| | | Min. | Typ. | Max. | | |
| Horizontal Display Area | Thd | | 800 | | DCLK | |
| DCLK Frequency | Fclk | 26.4 | 33.3 | 46.8 | MHz | |
| One Horizontal Line | Th | 862 | 1056 | 1200 | DCLK | |
| HS pulse width | Thpw | 1 | | 40 | DCLK | |
| HS Blanking | Thb | 46 | 46 | 46 | DCLK | |
| HS Front Porch | Thfp | 16 | 210 | 354 | DCLK | |

| Item | Symbol | Values | | | Unit | Remark |
|-----------------------|--------|--------|------|------|------|--------|
| | | Min. | Typ. | Max. | | |
| Vertical Display Area | Tvd | | 480 | | TH | |
| VS period time | Tv | 510 | 525 | 650 | TH | |
| VS pulse width | Tvpw | 1 | | 20 | TH | |
| VS Blanking | Tvb | 23 | 23 | 23 | TH | |
| VS Front Porch | Tvfp | 7 | 22 | 147 | TH | |

Horizontal input timing diagram




Vertical input timing diagram




2.3.3 Power Sequence

POWER ON





POWER OFF



3. QUALITY ASSURANCE SYSTEM

3.1 Quality Assurance Flow Chart




| Item | Customer | Sales | R&D | Q.A | Manufacturing | Product control | Purchase | Inventory control |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----|-----|-------------------------------------------------------------------------|-----------------|----------|-------------------|
| Sales Service |  <pre> graph TD Info[Info] --> Claim[Claim] Claim --> Analysis[Analysis report] Claim --> Failure[Failure analysis] Failure --> Corrective[Corrective action] Corrective --> Tracking[Tracking] </pre> | | | | | | | |
| Q.A Activity | 1. ISO 9001 Maintenance Activities 3. Equipment calibration 5. Standardization Management | | | | 2. Process improvement proposal 4. Education And Training Activities | | | |

3.2. Inspection Specification


- ◆Scope : The document shall be applied to TFT-LCD Module for 3.5" ~10" (Ver.B01).
- ◆Inspection Standard : MIL-STD-105E Table Normal Inspection Single Sampling Level II.
- ◆Equipment : Gauge 、 MIL-STD 、 Powertip Tester 、 Sample
- ◆Defect Level : Major Defect AQL : 0.4 ; Minor Defect AQL : 1.5
- ◆OUT Going Defect Level : Sampling.
- ◆Standard of the product appearance test :

a. Manner of appearance test :

- (1). The test best be under 20W×2 fluorescent light , and distance of view must be at 30 cm.
- (2). The test direction is base on about around 45° of vertical line.



(3). Definition of area.



A area : viewing area

B area : Outside of viewing area

(4). Standard of inspection : (Unit : mm)



◆Specification For TFT-LCD Module 3, 5" ~10" :

(Ver.B01)

| NO | Item | Criterion | Level | | | | | | | | | | | | |
|------------|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--|-------------------|------------|------------|-----|----------|-----|-----------|-----|-------|-----|-------|
| 01 | Product condition | 1. 1 The part number is inconsistent with work order of production. | Major | | | | | | | | | | | | |
| | | 1. 2 Mixed product types. | Major | | | | | | | | | | | | |
| | | 1. 3 Assembled in inverse direction. | Major | | | | | | | | | | | | |
| 02 | Quantity | 2. 1 The quantity is inconsistent with work order of production. | Major | | | | | | | | | | | | |
| 03 | Outline dimension | 3. 1 Product dimension and structure must conform to structure diagram. | Major | | | | | | | | | | | | |
| 04 | Electrical Testing | 4. 1 Missing line character and icon. | Major | | | | | | | | | | | | |
| | | 4. 2 No function or no display. | Major | | | | | | | | | | | | |
| | | 4. 3 Display malfunction. | Major | | | | | | | | | | | | |
| | | 4. 4 LCD viewing angle defect. | Major | | | | | | | | | | | | |
| | | 4. 5 Current consumption exceeds product specifications. | Major | | | | | | | | | | | | |
| 05 | Dot defect (Bright dot 、 Dark dot) On -display | <table><tr><th colspan="2">Item</th><th>Acceptance (Q'ty)</th></tr><tr><td rowspan="4">Dot Defect</td><td>Bright Dot</td><td>≤ 4</td></tr><tr><td>Dark Dot</td><td>≤ 5</td></tr><tr><td>Joint Dot</td><td>≤ 3</td></tr><tr><td>Total</td><td>≤ 7</td></tr></table> 5. 1 Inspection pattern : full white , full black , Red , Green and blue screens. 5. 2 It is defined as dot defect if defect area > 1/2 dot. 5. 3 The distance between two dot defect ≥5 mm. | Item | | Acceptance (Q'ty) | Dot Defect | Bright Dot | ≤ 4 | Dark Dot | ≤ 5 | Joint Dot | ≤ 3 | Total | ≤ 7 | Minor |
| Item | | Acceptance (Q'ty) | | | | | | | | | | | | | |
| Dot Defect | Bright Dot | ≤ 4 | | | | | | | | | | | | | |
| | Dark Dot | ≤ 5 | | | | | | | | | | | | | |
| | Joint Dot | ≤ 3 | | | | | | | | | | | | | |
| | Total | ≤ 7 | | | | | | | | | | | | | |


◆Specification For TFT-LCD Module 3, 5" ~10" :

(Ver.B01)



| NO | Item | Criterion | Level | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|-------------------|--|--------|--------|------------------|--------|--------|-------------------------|---|-------------------------|---|---------------|---|------------|-----------|-------------------|-------|--------|--------|-----|---------------|--------|--------|---------------|----------------------|---|--------------|----------------------|---|-----|------------|---------------|-------|--|---|--|-------|
| 06 | <p>Black or white dot、scratch、contamination</p> <p>Round type</p>  <p>$\Phi=(x+y) / 2$</p> <p>Line type</p>  | <p>6. 1 Round type (Non-display or display) :</p> <table><tr><th rowspan="2">Dimension (diameter : Φ)</th><th colspan="2">Acceptance (Q'ty)</th></tr><tr><th>A area</th><th>B area</th></tr><tr><td>$\Phi \leq 0.25$</td><td>Ignore</td><td rowspan="4">Ignore</td></tr><tr><td>$0.25 < \Phi \leq 0.50$</td><td>5</td></tr><tr><td>$\Phi > 0.50$</td><td>0</td></tr><tr><td>Total</td><td>5</td></tr></table> <p>6. 2 Line type(Non-display or display) :</p> <table><tr><th rowspan="2">Length (L)</th><th rowspan="2">Width (W)</th><th colspan="2">Acceptance (Q'ty)</th></tr><tr><th>A area</th><th>B area</th></tr><tr><td>---</td><td>$W \leq 0.03$</td><td>Ignore</td><td rowspan="4">Ignore</td></tr><tr><td>$L \leq 10.0$</td><td>$0.03 < W \leq 0.05$</td><td>4</td></tr><tr><td>$L \leq 5.0$</td><td>$0.05 < W \leq 0.10$</td><td>2</td></tr><tr><td>---</td><td>$W > 0.10$</td><td>As round type</td></tr><tr><td colspan="2">Total</td><td>5</td><td></td></tr></table> | Dimension (diameter : Φ) | Acceptance (Q'ty) | | A area | B area | $\Phi \leq 0.25$ | Ignore | Ignore | $0.25 < \Phi \leq 0.50$ | 5 | $\Phi > 0.50$ | 0 | Total | 5 | Length (L) | Width (W) | Acceptance (Q'ty) | | A area | B area | --- | $W \leq 0.03$ | Ignore | Ignore | $L \leq 10.0$ | $0.03 < W \leq 0.05$ | 4 | $L \leq 5.0$ | $0.05 < W \leq 0.10$ | 2 | --- | $W > 0.10$ | As round type | Total | | 5 | | Minor |
| Dimension (diameter : Φ) | Acceptance (Q'ty) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | A area | B area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\Phi \leq 0.25$ | Ignore | Ignore | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $0.25 < \Phi \leq 0.50$ | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\Phi > 0.50$ | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Total | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Length (L) | Width (W) | Acceptance (Q'ty) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | A area | B area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| --- | $W \leq 0.03$ | Ignore | Ignore | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $L \leq 10.0$ | $0.03 < W \leq 0.05$ | 4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $L \leq 5.0$ | $0.05 < W \leq 0.10$ | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| --- | $W > 0.10$ | As round type | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Total | | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 07 | Polarizer Bubble | <table><tr><th rowspan="2">Dimension (diameter : Φ)</th><th colspan="2">Acceptance (Q'ty)</th></tr><tr><th>A area</th><th>B area</th></tr><tr><td>$\Phi \leq 0.25$</td><td>Ignore</td><td rowspan="4">Ignore</td></tr><tr><td>$0.25 < \Phi \leq 0.50$</td><td>4</td></tr><tr><td>$0.50 < \Phi \leq 0.80$</td><td>1</td></tr><tr><td>$\Phi > 0.80$</td><td>0</td></tr><tr><td>Total</td><td>5</td><td></td></tr></table> | Dimension (diameter : Φ) | Acceptance (Q'ty) | | A area | B area | $\Phi \leq 0.25$ | Ignore | Ignore | $0.25 < \Phi \leq 0.50$ | 4 | $0.50 < \Phi \leq 0.80$ | 1 | $\Phi > 0.80$ | 0 | Total | 5 | | Minor | | | | | | | | | | | | | | | | | | | | |
| Dimension (diameter : Φ) | Acceptance (Q'ty) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | A area | B area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\Phi \leq 0.25$ | Ignore | Ignore | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $0.25 < \Phi \leq 0.50$ | 4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $0.50 < \Phi \leq 0.80$ | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\Phi > 0.80$ | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Total | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

◆Specification For TFT-LCD Module 3.5" ~10" :

(Ver.B01)

| NO | Item | Criterion | Level | | | | | | | | | |
|----------|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---|---|----------|--------------------------------|--------------|----------|------------------------------------------|----------------------|--|
| 08 | The crack of glass | <p>Symbols :</p> <div> <div> <p>X : The length of crack</p> <p>Z : The thickness of crack</p> <p>t : The thickness of glass</p> </div> <div> <p>Y : The width of crack.</p> <p>W : terminal length</p> <p>a : LCD side length</p> </div> </div> | Minor | | | | | | | | | |
| | | <p>8.1 General glass chip :</p> <p>8.1.1 Chip on panel surface and crack between panels:</p> <div>  </div> | | | | | | | | | | |
| | | <table> <tr> <th>X</th> <th>Y</th> <th>Z</th> </tr> <tr> <td>$\leq a$</td> <td>Crack can't enter viewing area</td> <td>$\leq 1/2 t$</td> </tr> <tr> <td>$\leq a$</td> <td>Crack can't exceed the half of SP width.</td> <td>$1/2 t < Z \leq 2 t$</td> </tr> </table> | X | Y | Z | $\leq a$ | Crack can't enter viewing area | $\leq 1/2 t$ | $\leq a$ | Crack can't exceed the half of SP width. | $1/2 t < Z \leq 2 t$ | |
| X | Y | Z | | | | | | | | | | |
| $\leq a$ | Crack can't enter viewing area | $\leq 1/2 t$ | | | | | | | | | | |
| $\leq a$ | Crack can't exceed the half of SP width. | $1/2 t < Z \leq 2 t$ | | | | | | | | | | |

◆Specification For TFT-LCD Module 3.5" ~10" :
(Ver.B01)

| NO | Item | Criterion | Level | | | | | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---|-------|--------------|--------------------------------|----------------|--------------|------------------------------------------|----------------------|--------------|
| 08 | The crack of glass | <p>Symbols :</p> <p>X : The length of crack Z : The thickness of crack t : The thickness of glass</p> <p>Y : The width of crack. W : terminal length a : LCD side length</p> <hr/> <p>8.1.2 Corner crack :</p>  <table><tr><th>X</th><th>Y</th><th>Z</th></tr><tr><td>$\leq 1/5 a$</td><td>Crack can't enter viewing area</td><td>$Z \leq 1/2 t$</td></tr><tr><td>$\leq 1/5 a$</td><td>Crack can't exceed the half of SP width.</td><td>$1/2 t < Z \leq 2 t$</td></tr></table> | X | Y | Z | $\leq 1/5 a$ | Crack can't enter viewing area | $Z \leq 1/2 t$ | $\leq 1/5 a$ | Crack can't exceed the half of SP width. | $1/2 t < Z \leq 2 t$ | Minor |
| | | X | Y | Z | | | | | | | | |
| $\leq 1/5 a$ | Crack can't enter viewing area | $Z \leq 1/2 t$ | | | | | | | | | | |
| $\leq 1/5 a$ | Crack can't exceed the half of SP width. | $1/2 t < Z \leq 2 t$ | | | | | | | | | | |
| <p>8.2 Protrusion over terminal :</p> <p>8.2.1 Chip on electrode pad :</p>  <table><tr><th></th><th>X</th><th>Y</th><th>Z</th></tr><tr><td>Front</td><td>$\leq a$</td><td>$\leq 1/2 W$</td><td>$\leq t$</td></tr><tr><td>Back</td><td>$\leq a$</td><td>$\leq W$</td><td>$\leq 1/2 t$</td></tr></table> | | X | Y | Z | Front | $\leq a$ | $\leq 1/2 W$ | $\leq t$ | Back | $\leq a$ | $\leq W$ | $\leq 1/2 t$ |
| | X | Y | Z | | | | | | | | | |
| Front | $\leq a$ | $\leq 1/2 W$ | $\leq t$ | | | | | | | | | |
| Back | $\leq a$ | $\leq W$ | $\leq 1/2 t$ | | | | | | | | | |

◆ Specification For TFT-LCD Module 3.5" ~10" :

(Ver.B01)

| NO | Item | Criterion | Level | | | | | | | | | | | | |
|--------------|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---|---|--------------|----------|----------|---|---|---|----------|--------------|----------|-------|
| 08 | The crack of glass | <p>Symbols :</p> <div> <div> <p>X : The length of crack</p> <p>Z : The thickness of crack</p> <p>t : The thickness of glass</p> </div> <div> <p>Y : The width of crack.</p> <p>W : terminal length</p> <p>a : LCD side length</p> </div> </div> <hr/> <p>8.2.2 Non-conductive portion :</p> <table border="1"> <tr> <td>X</td> <td>Y</td> <td>Z</td> </tr> <tr> <td>$\leq 1/3 a$</td> <td>$\leq W$</td> <td>$\leq t$</td> </tr> </table> <p>☉ If the chipped area touches the ITO terminal, over 2/3 of the ITO must remain and be inspected according to electrode terminal specifications.</p> <p>8.2.3 Glass remain :</p> <table border="1"> <tr> <td>X</td> <td>Y</td> <td>Z</td> </tr> <tr> <td>$\leq a$</td> <td>$\leq 1/3 W$</td> <td>$\leq t$</td> </tr> </table> | X | Y | Z | $\leq 1/3 a$ | $\leq W$ | $\leq t$ | X | Y | Z | $\leq a$ | $\leq 1/3 W$ | $\leq t$ | Minor |
| | | X | Y | Z | | | | | | | | | | | |
| $\leq 1/3 a$ | $\leq W$ | $\leq t$ | | | | | | | | | | | | | |
| X | Y | Z | | | | | | | | | | | | | |
| $\leq a$ | $\leq 1/3 W$ | $\leq t$ | | | | | | | | | | | | | |

4. RELIABILITY TEST

4.1 Reliability Test Condition

(Ver.B01)

| NO. | TEST ITEM | TEST CONDITION | |
|----------------------------------------------------------|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| 1 | High Temperature Storage Test | Keep in +80 ±2℃ 96 hrs Surrounding temperature, then storage at normal condition 4hrs. | |
| 2 | Low Temperature Storage Test | Keep in -30 ±2℃ 96 hrs Surrounding temperature, then storage at normal condition 4hrs. | |
| 3 | High Temperature / High Humidity Storage Test | Keep in +60 ℃ / 90% R.H duration for 96 hrs Surrounding temperature, then storage at normal condition 4hrs. (Excluding the polarizer) | |
| 4 | Temperature Cycling Storage Test | <div style="text-align: center;"><div><div>-30℃ → +25℃ → +80℃ → +25℃</div><div>(30mins) (5mins) (30mins) (5mins)</div><div>← 10 Cycle →</div></div> Surrounding temperature, then storage at normal condition 4hrs.</div> | |
| 5 | ESD Test | Air Discharge: Apply 2 KV with 5 times Discharge for each polarity +/- | Contact Discharge: Apply 250 V with 5 times discharge for each polarity +/- |
| | | 1. Temperature ambiance : 15℃ ~35℃ 2. Humidity relative : 30% ~60% 3. Energy Storage Capacitance(Cs+Cd) : 150pF±10% 4. Discharge Resistance(Rd) : 330Ω±10% 5. Discharge, mode of operation : Single Discharge (time between successive discharges at least 1 sec) (Tolerance if the output voltage indication : ±5%) | |
| 6 | Vibration Test (Packaged) | 1. Sine wave 10~55 Hz frequency (1 min/sweep) 2. The amplitude of vibration :1.5 mm 3. Each direction (X、Y、Z) duration for 2 Hrs | |
| 7 | Drop Test (Packaged) | | |
| | | Packing Weight (Kg) | Drop Height (cm) |
| | | 0 ~ 45.4 | 122 |
| | | 45.4 ~ 90.8 | 76 |
| | | 90.8 ~ 454 | 61 |
| | | Over 454 | 46 |
| Drop Direction :※1 corner / 3 edges / 6 sides each 1time | | | |

5. PRECAUTION RELATING PRODUCT HANDLING

5.1 SAFETY

- 5.1.1 If the LCD panel breaks , be careful not to get the liquid crystal to touch your skin.
- 5.1.2 If the liquid crystal touches your skin or clothes , please wash it off immediately by using soap and water.

5.2 HANDLING

- 5.2.1 Avoid any strong mechanical shock which can break the glass.
- 5.2.2 Avoid static electricity which can damage the CMOS LSI—When working with the module , be sure to ground your body and any electrical equipment you may be using.
- 5.2.3 Do not remove the panel or frame from the module.
- 5.2.4 The polarizing plate of the display is very fragile. So , please handle it very carefully ,do not touch , push or rub the exposed polarizing with anything harder than an HB pencil lead (glass , tweezers , etc.)
- 5.2.5 Do not wipe the polarizing plate with a dry cloth , as it may easily scratch the surface of plate.
- 5.2.6 Do not touch the display area with bare hands , this will stain the display area.
- 5.2.7 Do not use ketonics solvent & aromatic solvent. Use with a soft cloth soaked with a cleaning naphtha solvent.
- 5.2.8 To control temperature and time of soldering is $320 \pm 10^{\circ}\text{C}$ and 3-5 sec.
- 5.2.9 To avoid liquid (include organic solvent) stained on LCM .

5.3 STORAGE

- 5.3.1 Store the panel or module in a dark place where the temperature is $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and the humidity is below 65% RH.
- 5.3.2 Do not place the module near organics solvents or corrosive gases.
- 5.3.3 Do not crush , shake , or jolt the module.

5.4 TERMS OF WARRANTY

- 5.4.1 Applicable warrant period
The period is within thirteen months since the date of shipping out under normal using and storage conditions.
- 5.4.2 Unaccepted responsibility
This product has been manufactured to your company's specification as a part for use in your company's general electronic products. It is guaranteed to perform according to delivery specifications. For any other use apart from general electronic equipment , we cannot take responsibility if the product is used in nuclear power control equipment , aerospace equipment , fire and security systems or any other applications in which there is a direct risk to human life and where extremely high levels of reliability are required.

[illegible]

| | | | | | | |
|-----|----------------|---------|------------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| 007 | | | | PART NO: | <div><div><div><div></div><div></div><div></div><div></div></div><div></div><div></div></div><div>久正光電股份有限公司 POWER TIP TECHNOLOGY CORPORATION</div></div> | Drawing Title |
| 006 | | | | PH800480T013-IHB | | |
| 005 | | | | DRAWING NAME : | | |
| 004 | MODIFY DRAWING | Kevin | 2017/03/10 | LMD-PH800480T013-IHB | | |
| 003 | MODIFY DRAWING | Kevin | 2016/11/30 | TITLE: | | |
| 002 | MODIFY DRAWING | Terry | 2016/09/14 | LCD MODULE DRAWING | | |
| 001 | NEW DRAWING | Terry | 2016/07/13 | | | |
| REV | REV BY | REVISER | DATE | | | |

Ver.001

Documents NO.

PKG-PH800480T013-IHB

LCM包裝規格書

LCM Packaging Specifications

Approve

Check

Contact

Oliver

Stone

Kevin


1.包裝材料規格表 (Packaging Material) : (per carton)

| No. | Item | Model | Dimensions (mm) | 1Pcs Weight | Quantity | Total Weight |
|-----|---------------------------|------------------|----------------------|-------------|----------|--------------|
| 1 | 成品 (LCM) | PH800480T013-IHB | 164.9 X 100.0 X 4.95 | 0.168 | 60 | 10.08 |
| 2 | 靜電袋(1)Antistatic Bag | BAG240170ARABA | 240 X 170 | 0.0048 | 60 | 0.288 |
| 3 | 上蓋(2)EPE | FOAM000000078 | 310 X 250 X 90 | 0.1 | 4 | 0.4 |
| 4 | 下座(3)EPE | FOAM000000079 | 310 X 250 X 100 | 0.17 | 4 | 0.68 |
| 5 | 海綿墊(4)Foam Rubber Cushion | OTFOAM00006ABA | 290 X 240 X 10 | 0.0058 | 4 | 0.0232 |
| 6 | 外紙箱(5)Carton | BX52732536CCBA | 527 X 325 X 360 | 1.092 | 1 | 1.092 |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |

2.一 整箱總重量 (Total LCD Weight in carton) : 12.56 Kg±10%

3.單箱數量規格表 (Packaging Specifications and Quantity) :

(1)Total LCD quantity in carton : quantity per box 15 x no of boxes 4 = 60



特 記 事 項 (REMARK)

4. 包裝數量不足時需以EPE(舒美墊)填補空槽
EPE:OTFOAMEP0003BA自裁成
(166.5X109.0X10mm)



ALL TECHNOLOGIES. ALL COMPETENCIES. ONE SPECIALIST.



DATA MODUL AG
Landsberger Straße 322
DE-80687 Munich
Phone: +49-89-56017-0

DATA MODUL WEIKERSHEIM GMBH
Lindenstraße 8
DE-97990 Weikersheim
Phone: +49-7934-101-0



More information and worldwide locations can be found at

www.data-modul.com