



VESTEL

SPECIFICATION

PR43B-4F

43.0" - UHD

Version: 1.0

Date: 03.05.2022

Note: This specification is subject to change without prior notice

PR43B-4F |

DISPLAY

| | |
|--------------------------|---|
| Screen Size | 43" |
| Backlight Type | Slim DLED |
| Brightness (typical) | 700 cd/m ² |
| Native Resolution | 3840 x 2160 (16:9) - UHD |
| Contrast Ratio (typical) | 1200:1(typ.) |
| Dynamic Contrast Ratio | 70000:1 |
| Panel Life Time (Min.) | 50000 Hrs |
| Response Time (typical) | 8 ms |
| Active Area (H x V) | 941.184(H) x 529.416(V) |
| Viewing Angle | 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10 |
| Color Value | 1.07 G (8 bit + FRC) |
| Screen Treatment | 3H |
| Haze Level | 1% |
| Refresh Rate | 60 Hz |
| Orientation | Landscape / Portrait |
| Operation Hours | 24 / 7 |
| Area of Usage | Indoor |

REAR I/O

| | |
|------------------|---|
| RGB Input | VGA(DE-15F) |
| RGB Output | N/A |
| Video Input | 4xHDMI2.0, DP1.2a, 2xUSB2.0, USB2.0(Internal) |
| Video Output | HDMI2.0, DP1.2a |
| Audio Input | Line In L/R |
| Audio Output | Headphone, Optic SPDIF |
| External Control | RS232(DE-9F), Ethernet(RJ45), Service(RJ12) |
| External Sensor | RJ12 |

ENVIRONMENTAL CONDITIONS

| | |
|-----------------------|--------|
| Operating Temperature | 0-40°C |
| Operating Humidity | 10-90% |

POWER CONSUMPTION

| | |
|--------------|--------|
| Typical | 128 W |
| Deep Standby | ≤0.5 W |

ACCESSORY

| | |
|----------|---|
| Standard | QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable |
|----------|---|

BUILT-IN SYSTEM

| | |
|-----------------|-----------|
| Mainboard Model | 17MB135VS |
|-----------------|-----------|

MECHANICAL

| | |
|----------------------------|--|
| Product Dimensions (WxDxH) | "963 x 83 x 555 mm with OPS/SDM 963 x 63 x 555 mm without OPS/SDM" |
| Package Dimensions (WxDxH) | 1050 x 178 x 718 mm |
| Product Weight | 10.4kg |
| Package Weight | 13.5kg |
| Vesa Mounting | 200 mm(W) x 200 mm(H) M6 |
| Bezel Width | 6/6/6/9 mm |

POWER

| | |
|--------------|------------------------------|
| Power Supply | 110 VAC - 240 VAC - 50/60 Hz |
|--------------|------------------------------|

FEATURES

| | |
|---------------------|---|
| Main Features | Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD Rotation, NoSignalPowerOff, Screen Saver, Pixel shift, Scheduler, Videowall support, Remote control via LAN, Real Time Clock |
| Mechanical Features | Joystick, Rocker Switch, Detachable Power Cable, Detachable Logo, Internal Usb Cover, 30-degrees Tilting Installation |
| Optional Features | SDM or OPS compatibility, Embedded IR, IR extender option |
| Speaker | 2x8 W |

CERTIFICATION

| | |
|--------|-----|
| Safety | Yes |
| EMC | Yes |
| CE | Yes |



ALL TECHNOLOGIES. ALL COMPETENCIES. ONE SPECIALIST.



DATA MODUL AG
Landsberger Straße 322
DE-80687 Munich
Phone: +49-89-56017-0

DATA MODUL WEIKERSHEIM GMBH
Lindenstraße 8
DE-97990 Weikersheim
Phone: +49-7934-101-0



More information and worldwide locations can be found at

www.data-modul.com