



SPECIFICATION



TM101JDHP01

10.1" – 1280 x 800 – LVDS

Version: 2.6

Date: 25.06.2019

Note: This specification is subject to change without prior notice

www.data-modul.com

MODEL NO : TM101JDHP01**MODEL VERSION:** 00**SPEC VERSION :** 2.6**ISSUED DATE:** 2019-06-25

- Preliminary Specification
 Final Product Specification

Customer : _____

Approved by	Notes

TIANMA Confirmed :

Prepared by	Checked by	Approved by
Junwen Du	Longping Deng	KEVIN

This technical specification is subjected to change without notice

Table of Contents

Table of Contents	2
Record of Revision.....	3
1 General Specifications.....	4
2 Input/Output Terminals	5
3 Absolute Maximum Ratings.....	7
4 Electrical Characteristics	8
5 Timing Chart.....	10
6 Optical Characteristics	14
7 Environmental / Reliability Test.....	17
8 Mechanical Drawing	18
9 Packing Drawing	19
10 Precautions for Use of LCD Modules.....	20

Record of Revision

Rev	Issued Date	Description	Editor
1.0	2015-04-13	Preliminary Specification Release	Yuelong.Zhou
1.1	2015-04-14	Modify the LED lifetime	Yuelong.Zhou
1.2	2015-04-15	Modify the LCM model number	Yuelong.Zhou
1.3	2015-04-30	Modify the Vcom	Yuelong.zhou
1.4	2015-05-13	Modify the LED lifetime	Yuelong.Zhou
1.5	2015-09-28	Update the Mechanical Drawing and Optical Characteristics	Junwen Du
2.0	2016-01-29	Final Specification Release	Junwen Du
2.1	2016-02-01	Update the reliability test	Junwen Du
2.2	2016-04-27	Update the power supply current	Junwen Du
2.3	2017-08-18	Change the Requirements on Environmental Protection in page 4.Ver 2.2 and Ver 2.3 have same display performance (About Electric & Optical & Mechanical parts)	Junwen Du
2.4	2018-10-25	Update the pin description	Junwen Du
2.5	2019-03-04	Update the Voltage Min and Max value in page 8 and NTSC Min value in page 14	Junwen Du
2.6	2019-06-25	Change packing Drawing	Longping.Deng

1 General Specifications

	Feature	Spec
Display Spec.	Size	10.1 inch
	Resolution	1280(RGB) × 800
	Technology Type	a-si TFT
	Pixel Configuration	R.G.B. Vertical Stripe
	Pixel pitch(mm)	0.1695x0.1695
	Display Mode	TM, Normally Black
	Surface Treatment	HC
Mechanical Characteristics	LCM (W x H x D) (mm)	229.46 x 149.10 x 2.50
	Active Area(mm)	216.96 x 135.60
	With /Without TSP	Without TSP
	Matching Connection Type	F62240-H1210A
	LED Numbers	33 LED
	Weight (g)	180g
Electrical Characteristics	Interface	LVDS 8-bit
	Color Depth	16.7M
	Driver IC	ST5821CA*3 + ST5084CA*1

Note 1: Viewing direction for best image quality is different from TFT definition. There is a 180 degree shift.

Note 2: Requirements on Environmental Protection: Q/S0002 & UL & MSDS.

Note 3: LCM weight tolerance: ± 5%

2 Input/Output Terminals

Recommended connector: F62240-H1210A

Pin	Symbol	I/O	Description	Remark
1	Vcom	P	Common Voltage	
2	VDD	P	Power Supply	
3	VDD	P	Power Supply	
4	NC		No Connect	
5	NC		No Connect	
6	NC		No Connect	
7	GND	P	Ground	
8	Rxin0-	I	-LVDS differential data input	R0~R5,G0
9	Rxin0+	I	+LVDS differential data input	
10	GND	P	Ground	
11	Rxin1-	I	-LVDS differential data input	G1~G5,B0,B1
12	Rxin1+	I	+LVDS differential data input	
13	GND	P	Ground	
14	Rxin2-	I	-LVDS differential data input	B2~B5,HS,VS, DE
15	Rxin2+	I	+LVDS differential data input	
16	GND	P	Ground	
17	RxCLK-	I	-LVDS differential clock input	LVDS clock
18	RxCLK+	I	+LVDS differential clock input	
19	GND	P	Ground	
20	Rxin3-	I	-LVDS differential data input	R6,R7,G6,G7, B6,B7
21	Rxin3+	I	+LVDS differential data input	
22	GND	P	Ground	
23	NC		No Connect	
24	NC		No Connect	
25	GND	P	Ground	
26	NC		No Connect	
27	NC		No Connect	
28	NC		No Connect	

The information contained herein is the exclusive property of TIANMA MICRO-ELECTRONICS Corporation and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of TIANMA MICRO-ELECTRONICS Corporation.

29	AVDD	P	Power for Analog Circuit	
30	GND	P	Ground	
31	LED-		LED Cathode	
32	LED-		LED Cathode	
33	NC		No Connect	
34	NC		No Connect	
35	VGL	P	Gate OFF Voltage	
36	NC		No Connect	
37	NC		No Connect	
38	VGH		Gate ON Voltage	
39	LED+		LED Anode	
40	LED+		LED Anode	

Note1: P: Power/GND; I: input pin; O: output

3 Absolute Maximum Ratings

GND=0V

Item	Symbol	MIN	MAX	Unit	Remark
Power Voltage	VCC	-0.3	3.9	V	Note1
Power For Analog Circuit	AVDD	-0.3	14	V	
Gate On Voltage	VGH	-0.3	42	V	
Gate Off Voltage	VGL	-19	0.3	V	
Operating Temperature	Top	-10	50	°C	
Storage Temperature	Tst	-20	60	°C	
Relative Humidity Note2	RH	--	≤95	%	Ta≤40°C
		--	≤85	%	40°C < Ta≤50°C
		--	≤55	%	50°C < Ta≤60°C
		--	≤36	%	60°C < Ta≤70°C
		--	≤24	%	70°C < Ta≤80°C
Absolute Humidity	AH	--	≤70	g/m ³	Ta>70°C

Table 3 Absolute Maximum Ratings

Note1: Input voltage include Rxin0-/ Rxin0+, Rxin1-/ Rxin1+, Rxin2-/ Rxin2+, Rxin3-/ Rxin3+, RxCLK-/ RxCLK+.

Note2: Ta means the ambient temperature.

It is necessary to limit the relative humidity to the specified temperature range.

Condensation on the module is not allowed.

4 Electrical Characteristics

4.1 Driving TFT LCD Panel

GND=0V, Ta=25°C

Item	Symbol	Min	Typ	Max	Unit	Remark
POWER Supply Voltage	VDD	3.00	3.30	3.60	V	
Power For Analog Circuit	AVDD	10.8	11	11.2	V	
Gate On Voltage	VGH	22	23	24	V	
Gate Off Voltage	VGL	-7.5	-7.0	-6.5	V	
Common Voltage	Vcom	4.2	4.3	4.4		
Input Signal Voltage	Low Level	VIL	GND	-	0.2xVDD	V
	High Level	VIH	0.8xVDD	-	VDD	V
Output Signal Voltage	Low Level	VIL	GND	-	0.2xVDD	V
	High Level	VIH	0.8xVDD	-	VDD	V

4.2 Driving Backlight


Ta=25°C

Item	Symbol	Min	Typ	Max	Unit	Remark
Forward Current	I _F	--	220	330	mA	
Forward Current Voltage	V _F	9.0	9.6	10.8	V	
LED lifetime	--	20000	30000	--	Hr	

Note1: The LED driving condition is defined for each LED module.

Note2: Under LCM operating, the stable forward current should be input. And forward voltage is for reference only.

Note3: Optical performance should be evaluated at Ta=25°C only If LED is driven by high current, high ambient temperature & humidity condition. The life time of LED will be reduced. Operating life means brightness goes down to 50% initial brightness. Typical operating life time is estimated data.



4.3 Power Supply Current

AGND=GND=0V, Ta = 25°C


Item	Symbol	Condition	Min	Typ	Max	Unit	Remark
Power Supply Current	I_{DVDD}	VCC=3.3V	-	54.1	65	mA	
	I_{AVDD}		-	47.6	55	mA	
	I_{VGH}		-	663	700	uA	
	I_{VGL}		-	663	700	uA	
	I_{VCOM}			2	3	uA	

NOTES: White picture, frame rate 60Hz.


5 Timing Chart

5.1 Power sequence

Power on



Power off




5.2 LVDS signal timing characteristic


Electrical characteristics

Parameter	Symbol	Value			Unit	Note
		min	typ	max		
LVDS differential input high threshold voltage	R_{xVTH}	-	-	+100	mV	$R_{xVCM}=1.2V$
LVDS differential input low threshold voltage	R_{xVTL}	-100	-	-	mV	
LVDS differential input common mode voltage	R_{xVCM}	0.7	1.2	1.6	V	
LVDS differential voltage	V_{ID}	200	-	600	mV	

Single-end Signals




Differential Signal




5.3 Timing table

Parameter	Symbol	Value			Unit	Note
		min	typ	max		
CLK frequency	t_{clk}	62.6	68.2	78.1	Mhz	
Horizontal blanking time	t_{HBT}	20	69	164	t_{clk}	$t_{hbp} + t_{HFP}$
Horizontal black porch	t_{HBP}	5	5	$164 - t_{HFP}$	t_{clk}	
Horizontal display area	t_{HD}	1280	1280	1280	t_{clk}	
Horizontal front porch	t_{HFP}	15	64	159	t_{clk}	
Horizontal period	t_H	1300	1349	1444	t_{clk}	
Horizontal pulse width	t_{HPW}	1	1	256	t_{clk}	
Vertical blanking time	t_{VBT}	5	42	101	t_H	$t_{vbp} + t_{VFP}$
Vertical black porch	t_{VBP}	2	2	$101 - t_{VFP}$	t_H	
Vertical display area	t_{VD}	800	800	800	t_H	
Vertical front porch	t_{VFP}	3	40	99	t_H	
Vertical period	t_V	803	842	901	t_H	
Vertical pulse width	t_{VPW}	1	1	128	t_H	

Horizontal input timing




Vertical input timing



The information contained herein is the exclusive property of TIANMA MICRO-ELECTRONICS Corporation and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of TIANMA MICRO-ELECTRONICS Corporation.

5.4 LVDS data input format



Note1: SW:Setup and hold time
 Note2: $t_{LVSKM}=400ps$ at least.

6 Optical Characteristics


Item	Symbol	Condition	Min	Typ	Max	Unit	Remark
View Angles	θT	$CR \geq 10$	75	85	-	Degree	Note2,3
	θB		75	85	-		
	θL		75	85	-		
	θR		75	85	-		
Contrast Ratio	CR	$\theta=0^\circ$	600	800			Note 3
Response Time	T_{ON}	25°C	-	25	50	ms	Note 4
	T_{OFF}						
Chromaticity	White	x	Backlight is on	0.250	0.300	0.350	Note 1,5
		y		0.274	0.324	0.374	
	Red	x		0.530	0.580	0.630-	Note 1,5
		y		0.274	0.324	0.374	
	Green	x		0.299	0.349	0.399	Note 1,5
		y		0.538	0.588	0.638	
	Blue	x		0.104	0.154	0.204	Note 1,5
		y		0.045	0.095	0.145	
Uniformity	U		75	80	-	%	Note 6
NTSC			45	50	-	%	Note 5
Luminance	L		350	400	-	cd/m ²	Note 7

Test Conditions:

1. $I_F= 220$ mA, and the ambient temperature is 25°C.
2. The test systems refer to Note 1 and Note 2.


Note 1: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 Minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.



Note 2: Definition of viewing angle range and measurement system.

viewing angle is measured at the center point of the LCD by CONOSCOPE(ergo-80).



Note 3: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD is on the "White" state}}{\text{Luminance measured when LCD is on the "Black" state}}$$

“White state “: The state is that the LCD should drive by V_{white} .


“Black state”: The state is that the LCD should drive by V_{black} .

V_{white} : To be determined V_{black} : To be determined.

The information contained herein is the exclusive property of TIANMA MICRO-ELECTRONICS Corporation and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of TIANMA MICRO-ELECTRONICS Corporation.

Note 4: Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.



Note 5: Definition of color chromaticity (CIE1931)


Color coordinates measured at center point of LCD.

Note 6: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity (U)} = L_{\min} / L_{\max}$$

L-----Active area length W----- Active area width



L_{\max} : The measured Maximum luminance of all measurement position.

L_{\min} : The measured Minimum luminance of all measurement position.

Note 7: Definition of Luminance:

Measure the luminance of white state at center point.

7 Environmental / Reliability Test

No	Test Item	Condition	Remarks
1	High Temperature Operation	Ts= +50°C, 120hrs	IEC60068-2-1:2007 GB2423.2-2008
2	Low Temperature Operation	Ta= -10°C, 120hrs	IEC60068-2-1:2007 GB2423.1-2008
3	High Temperature Storage	Ta = +60°C, 120hrs	IEC60068-2-1:2007 GB2423.2-2008
4	Low Temperature Storage	Ta = -20°C, 120 hrs	IEC60068-2-1:2007 GB2423.1-2008
5	Storage at High Temperature and Humidity	Ta=+40°C, 90% RH 120 hours	IEC60068-2-78 :2001 GB/T2423.3—2006
6	Thermal Shock (non-operation)	-10°C 30 min~+50°C 30 min, Change time:5min, 20 Cycles	Start with cold temperature, End with high temperature, IEC60068-2-14:1984,G B2423.22-2002
7	ESD	C=100pF, R=1500Ω, 5points/panel Air:± 4KV, 5times, Contact:± 2KV, 5 times, (Environment: 15°C~35°C, 30%~60%, 86Kpa~106Kpa)	IEC61000-4-2:2001 GB/T17626.2-2006
8	Vibration Test	Stroke:1.5m Sweep:10Hz~55Hz~10Hz 2 hours for each direction of X.Y.Z. (6 hours for total)(Package condition)	IEC60068-2-6:1982 GB/T2423.10—1995
9	Mechanical Shock (Non OP)	100G 6ms, ± X,± Y,± Z 3times, for each direction	IEC60068-2-27:1987 GB/T2423.5—1995


Note1: Ts is the temperature of panel's surface.

Note2: Ta is the ambient temperature of sample.

Note3: Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

Note 4: In the standard condition, there shall be no practical problem that may affect the display function. After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.


8 Mechanical Drawing



The information contained herein is the exclusive property of TIANMA MICRO-ELECTRONICS Corporation and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of TIANMA MICRO-ELECTRONICS Corporation.

9 Packing Drawing

No	Item	Model (Materiel)	Dimensions(mm)	Unit Weight(Kg)	Quantity	Remark
1	LCM Module	TM101JDHP01-00	229.46×149.1×2.55mm	0.192	36	
2	Tray	PET (Transmit)	485×330×13.8	0.196	21	
3	Dust-Proof Bag	PE	700×545	0.046	1	
4	BOX	Corrugated Paper	520×345×74	0.369	3	
5	Desiccant	Desiccant	45×50	0.002	6	
6	Carton	Corrugated Paper	544×365×250	0.76	1	
7	Label	Label	100*52	0.001	1	
8	EPE	EPE	349.4*228.06*1.0	0.0013	18	
9	Total Weight	13kg+-5%				



The information contained herein is the exclusive property of TIANMA MICRO-ELECTRONICS Corporation and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of TIANMA MICRO-ELECTRONICS Corporation.

10 Precautions for Use of LCD Modules

10.1 Handling Precautions

10.1.1 The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

10.1.2 If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

10.1.3 Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

10.1.4 The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

10.1.5 If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

- Isopropyl alcohol
- Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
- Ketone
- Aromatic solvents

10.1.6 Do not attempt to disassemble the LCD Module.

10.1.7 If the logic circuit power is off, do not apply the input signals.

10.1.8 To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

10.1.8.1 Be sure to ground the body when handling the LCD Modules.

10.1.8.2 Tools required for assembly, such as soldering irons, must be properly ground.

10.1.8.3 To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

10.1.8.4 The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

10.2 Storage precautions

10.2.1 When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

10.2.2 The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0°C ~ 40°C Relatively humidity: ≤80%

10.2.3 The LCD modules should be stored in the room without acid, alkali and harmful gas.

10.3 Transportation Precautions

10.3.1 The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.



ALL TECHNOLOGIES. ALL COMPETENCIES. ONE SPECIALIST.



DATA MODUL AG
Landsberger Straße 322
DE-80687 Munich
Phone: +49-89-56017-0

DATA MODUL WEIKERSHEIM GMBH
Lindenstraße 8
DE-97990 Weikersheim
Phone: +49-7934-101-0



More information and worldwide locations can be found at

www.data-modul.com