



7.0 inch (17.8cm) Part-No. 12015571 eTD070W1201-INA-A (USB), G070Y2-L01 incl. easyTOUCH

Display

Panel Type Innolux G070Y2-L01 Resolution (pixel) / format 800 x 480/ wide Brightness (typical) 500 cd/m² TN, Normally White Display Mode **Customer Interface Display** LVDS Contrast ratio (typical) 550:1 Backlight LED

Glass and Touch

Cover glass 2mm Glare Glass, chemically strengthened, no treatment Printing RAL9005 organic, light-tight Dimensions according to outline drawing Touch sensor type 7.0" easyTOUCH 12012164 Active area touch sensor (W x H) 157.6 x 93.7 mm according to DATA MODUL Outgoing Specification 12005964 **Optical Specification** Touch Interface USB mXT640T

Assembling

Glass to touch Optically bonded Glass/Touch assembly to display AirGap-Bonding with 4 stripes industrial double-sided adhesive tape Touch Controllerboard mounted on rear side of TFT with metal bracket

Accessories

Touch Controller easyTOUCH mXT640T Driverless USB


Environmental conditions


Temperature (operating) -20 to 70 °C

Mechanical dimensions

Outline dimensions (W x H x T) 197.0 x 136.0 x 18.4 mm Detailed dimensions according to outline drawing Weight approx. 0.350 kg (±10%)









Weight: 350g \pm 10% Surface and lamination defects according DataModul Spec. 12005964